Smartjac Industries Inc. - Kanalvägen 1A 2nd floor SE-194 61 Upplands Väsby Sweden www.smartjac.com / www.smartjac.biz

1386 ISOProx® II Card



Brand: Smartjac Industries Inc **Product Code:** SMAH100143

Short Description

Low frequency, entry-level proximity cards for physical access control.

Description

HID Prox 125 kHz Credentials

1386 ISOProx® II Card

ISO-Thin, Imageable proximity card for access control.

Overview

The ISOProx II Card offers proximity card technology with photo identification capability on a single access control card. It is ISO 7810 compliant, with a nominal thickness of .030". The card features a graphics quality surface optimized for Photo ID printing, and is available in standard PVC construction, or a composite polyester/PVC construction for more demanding high wear and tear environments.

Like all HID ISO cards, the ISOProx II proximity card can be produced with visual security and anti-counterfeiting features such as holograms, ultra-violet fluorescent inks,

micro-printing, or a custom logo to quickly and easily identify genuine cards for ultimate access control.

When customizing cards using Re-Transfer Printers that fuse images to the surface of the card by applying heat and pressure (such as the Fargo HDP5000) we recommend the use of composite cards, which are better able to withstand the higher application temperatures.

Key Features of the ISOProx II Proximity Card

Offers proximity card technology with photo identification capability on a single access control card

Graphics quality surface for use with direct image printers Same size and thickness as a standard credit card Vertical or horizontal slot punch capability Lifetime warranty

Specifications Specifications

1386 ISOProx® II Proximity Card for Access Control

Typical Maximum* Read Range

ProxPoint® Plus reader-up to 2.5" (6.25 cm)

MiniProx® reader-up to 5" (12.5 cm)

ThinLine II® reader-up to 5" (12.5 cm)

ProxPro® reader-up to 7" (17.5 cm)

ProxPro® II reader-up to 8" (20 cm)

 $Prox80^{TM}$ -up to 5" (12.7 cm)

MaxiProx® reader-up to 20" (50 cm)

Dimensions

2.125" x 3.370" x 0.030" ± 0.003 " (5.4 x 8.6 x 0.076 ± 0.0076 cm)

Card Construction

Thin, flexible polyvinyl chloride (PVC) laminate or composite Polyester/PVC.

Warrarnty

^{*}Dependent on local installation conditions.

Lifetime