

1434 MIFARE® Keyfob



Brand: HID Global
Product Code: SMAH100150

Short Description

13.56 MHz Contactless KeyFob

Description

Overview

1434 MIFARE® Keyfob Smart Card

The rugged HID MIFARE® Keyfob smart card credential is ideally suited for a variety of applications and environments. These include vacation resorts, health spas, apartment buildings, club houses, as well as commercial offices where photo IDs are not required. The RF-programmable keyfob features the high quality and security benefits customers appreciate in HID FlexSmart 13.56 MHz MIFARE® smart card credentials. The Keyfob permits the encoding of a wide range of data and information. Securely separated sectors, each protected by a set of two keys and programmable access conditions, allow complex applications and provide for future expansion.

Manufactured to the highest quality standards, HID FlexSmart MIFARE® smart card products have the memory structure and capacity to store multiple applications on a single smart card credential. The data on the keyfob is protected with encryption keys used in the mutual authentication process. Therefore, no important data will be shared until the keyfob and reader have been mutually authenticated.

Key Features

High Security - MIFARE® smart card technology ensures mutual authentication, data encryption and unique 32-bit serial number.

Proven, Reliable Technology - Offers extremely consistent smart card read range. Use is unaffected by body shielding or variable environmental conditions, even when close to keys and coins.

Fast Processing and Data Communication - Transaction times are less than 100 milliseconds for a typical secure ticketing transaction.

Multiple Memory Types - Available in MIFARE® 1K and 4K.

Keyfob Flexibility and Convenience - Contemporary design enables easy attachment to a key, badge clip or badge lanyard.

Rugged, Double-Sealed Construction - Built to withstand harsh operating environments.

Customizable - Keyfob smart card credential can be customized by adding a company logo.

Specifications

Typical Maximum Read Range*

Up to 2" (5.0 cm)

Dimensions

1.725" x 1.197" x 0.215"
(4.38 cm x 3.04 cm x 0.55 cm)

Card Construction

Molded Polycarbonate, matte blue

Memory Type

EEPROM, 1 KByte (8,192 bits) or 4 KBytes (32,768 bits)

Multi-Application Memory

MIFARE® 1K: memory arranged in 16 64-byte sectors.

MIFARE® 4K: memory arranged in 40 sectors: 32 sectors of 64 bytes, 8 sectors of 256 bytes.

Warranty

Lifetime - see Sales Policy for complete details